

高级UPE食品输送软管 A3-015



应用:

■ 卫生级光滑内层对气味没有任何影响, 适用于各种食品饮料行业; 内层及外层均耐油脂及腐蚀性物质; 耐臭氧, 耐候性, 耐磨方面的极好性能; 软管与常用的清洗消毒剂相容, 可以用常规方法清洗或者用CIP 系统清洗。

技术参数:

- 内层: 高级UPE材质, 光滑, 对气味有任何影响, 耐油脂
- 增强层: 合成纤维 (特殊防真空设计)
- 外层: NBR材质, 蓝色
- 工作温度: -30℃至+95℃/-22°F至+203°F
- 可以用+130℃蒸汽清洗 (最多60分钟)
- 适用标准: 符合BFR III及FDA认证

Applications:

■ As a vacuum resistant construction with an integrated steel wire helix offer high quality at reasonable prices. The hygienically smooth, non-porous UPE lining free of plasticizers is absolutely neutral to taste and odour and thus suitable for various applications in the beverage and foodstuffs industry. They are resistant to commonly used cleaning and disinfecting products and can easily be cleaned conventionally or by CIP installations. Both, lining and cover are resistant to oil, fats and caustics

Technical description:

- Tube:white, non-porous, smooth UPE lining
- Reinforcements: synthetic fiber
- Cover:NBR-cover, resistant to ozone, weather, UV and abrasion
- Temperature:Absolutely neutral to taste and odour suitable for pure alcohol up to 98% Temperature range up to +85°C
- Can be steamed up to +130 °C (max. 60 minutes)
- Working pressure up to 12 bar
- Standard/Approval:Meets the recommendation XXI of BFR and FDA

高级UPE食品输送软管 BLAUDIECK LGDSU

产品编码 No.	内径		壁厚	工作压力	最小爆破压力	最小弯曲半径	重量
	in	mm	mm	bar	bar	mm	g/m
A3-015-1000	1	25	6.0	12	48	170	760
A3-015-1250	1-1/4	32	6.0	12	48	200	1.050
A3-015-1580	1-9/16	40	7.0	12	48	250	1.450
A3-015-2000	2	50	8.0	12	48	330	2.000
A3-015-2560	2-5/8	65	8.0	12	48	430	2.520
A3-015-3000	3	75	8.0	12	48	500	2.840
A3-015-3150	3-1/8	80	8.0	12	48	530	3.050
A3-015-4000	4	100	9.0	12	48	660	4.180

blueFuture
您身边的工业专家