

焊接管 A4-250



应用:

- 用于焊接设施。满足RMA IP-7标准里的R等级焊接管

技术参数:

- 内胶: EPDM合成橡胶适用于氧气和乙炔气体
- 增强层: 合成砂线螺旋缠绕
- 外胶: EPDM合成橡胶, 光面外胶
- 工作温度: -40° C 至49° C (-40° F 至120° F)

Applications:

- For welding service. Meets ARPM IP-7-2011 standard for Grade R welding hose

Technical description:

- Inner Tube: EPDM synthetic rubber compatible with oxygen and acetylene gases.
- Reinforcement: Spiral synthetic yarn
- Cover: EPDM synthetic rubber smooth surface
- Temperature Range: -40 C to 90 C (-40°F to 120°F)

焊接管 TWIN-LINE WELDING GRADE R-TYPE VD

产品编码 No.	内径		外径 mm	工作压力 bar	重量 kg/m	包装长度 m
	in	mm				
A4-250-0190	3/16"	4.8	11.2	13.8	0.19	152.4
A4-250-0250	1/4"	6.4	13.5	13.8	0.27	152.4
A4-250-0310	5/16"	7.9	15.0	13.8	0.33	152.4
A4-187-0380	3/8"	9.5	16.8	13.8	0.39	152.4

blueFuture

您身边的工业专家