

耐真空波纹特氟龙单管

A5-022



特性:

- 可耐受98%的化学品的输送/浸泡
- 可耐受真空负压

技术参数:

- 白色, 内壁光滑, 波纹PTFE单管, 坚固、灵活耐用
- 工作温度: -70℃至+260℃

Advantages:

- For transferring 98% chemicals and it could be soaked in chemical solvent.
- Withstand vacuum pressure

Technical description:

- White, Ripple PTFE tube, strong, flexible and durable
- Working temperature: - 70 C to + 260 C

耐真空波纹特氟龙单管 A5-022

产品编码 No.	内径		壁厚	外径	弯曲半径	耐真空
	in	mm	mm	mm	mm	bar
A5-022-0630	5/8"	16	1.5	22.5	60	0.9
A5-022-0750	3/4"	20	1.5	28	80	0.9
A5-022-1000	1"	25	1.5	33.5	100	0.9
A5-022-1250	1-1/4"	32	1.5	41.5	125	0.9
A5-022-1500	1-1/2"	38	2	54	140	0.9
A5-022-2000	2"	48	2	62	150	0.9
A5-022-2500	2-1/2"	63	2	82	200	0.9
A5-022-3000	3"	74	2.3	90	225	0.9
A5-022-4000	4"	98	3	124	275	0.9

