


光滑特氟龙软管

PSH



应用:

- 适用于制药、食品、化工、饮料等，几乎可以应用在任何行业

优点:

- 里层为平滑的PTFE 软管，外覆SS304 不锈钢编织
- 具有柔韧性高、零摩擦、耐高压和耐温广的优势
- 标准与防静电内衬可供选择

温度范围:

- -70℃至+260℃

认证标准:

- 符合FDA认证

Applications:

- For pharmaceutical, food, chemical, beverage and an almost endless list of applications

Advantages:

- Smooth bore PTFE hose, with 304 stainless steel over braid
- High performance product offering superb flexibility, zero friction, high pressure and a wide temperature range
- Virgin and anti-static liners available

Temperature:

- -70°C to +260°C

Standard/Approval:

- FDA

光滑特氟龙软管

PSH

产品编码	内径		壁厚	外径	工作压力	爆破压力	弯曲半径
No.	in	mm	mm	mm	bar	bar	mm
PSH-0190	0.19	4.89	0.9	7.87	276	828	51
PSH-0200	0.20	5.1	0.9	8.05	264	793	64
PSH-0260	0.26	6.7	0.8	9.35	224	669	76
PSH-0310	0.31	8	0.9	11.3	218	655	102
PSH-0330	0.33	8.4	0.6	11.05	207	621	102
PSH-0390	0.39	10	0.6	12.65	183	552	127
PSH-0410	0.41	10.3	0.9	13.44	183	552	133
PSH-0520	0.52	13.2	0.9	16.55	161	483	152
PSH-0540	0.54	13.6	0.9	17.15	161	483	150
PSH-0650	0.65	16.6	0.9	19.75	114	345	178
PSH-0780	0.78	19.8	0.9	22.96	103	310	203
PSH-0870	0.87	22.1	0.9	25.27	92	276	229
PSH-1030	1.03	26.1	0.9	29.25	80	241	305

