

网纹增强管 TR型

PX-016



应用:

- 作为一般配管用, 适用于水、油、药品、空气等各种流体
- 透明度高, 可确认流体, 放心可靠
- 内面耐油性优异, 更耐用
- 柔软性良好, 配管简便
- 胶管切割简单, 接头插接方便
- 符合RoHS2修正规制, 安全放心

技术参数:

- 主材质: 软质聚氯乙烯
- 加强材料: 聚酯丝
- 颜色: 蓝色透明带图案条+带蓝色竖线
- 包装: TR-4~25: 筒卷 TR-32~75: 薄膜卷
- 工作温度: -5℃至+60℃

优点:

- 柔软
- 透明
- 耐油
- 泵送用

Applications:

- As a general piping, it is suitable for various fluids such as water, oil, medicine, air, etc.
- High transparency, fluid can be confirmed, rest assured and reliable
- The inner surface has excellent oil resistance and is more durable
- Good flexibility and easy piping
- The hose is easy to cut, and the connector is easy to plug in
- Comply with RoHS2 revised regulations, safe and secure

Technical description:

- Main material: soft polyvinyl chloride
- Reinforcing material: polyester silk
- Color: blue transparent strip with pattern + blue vertical line
- Packing: TR-4~25: roll TR-32~75: film roll
- Working temperature: -5℃ to +60℃

Advantages:

- soft
- Transparent
- Oil resistant
- For pumping

网纹增强管 TR型

PX-016

产品编码 No.	内径		外径 mm	使用压力 Mpa		标准长度重量 kg/卷	标准长度 m	最小弯曲半径 mm
	in	mm		23℃	60℃			
PX-016-4	5/32"	4	9	0~1.5	0~1.0	7	100	15
PX-016-6	1/4"	6	11	0~1.5	0~1.0	9	100	20
PX-016-8	5/16"	8	13.5	0~1.5	0~1.0	13	100	35
PX-016-9	3/8"	9	15	0~1.5	0~1.0	15	100	45
PX-016-10	13/32"	10	16	0~1.2	0~1.0	16	100	45
PX-016-12	1/2"	12	18	0~1.2	0~0.8	19	100	55
PX-016-15	5/8"	15	22	0~1.0	0~0.8	27	100	80
PX-016-19	3/4"	19	26	0~1.0	0~0.6	16	50	95
PX-016-22	27/32"	21.5	29	0~1.0	0~0.6	20	50	120
PX-016-25	1"	25	33	0~1.0	0~0.6	25	50	140
PX-016-32	1-1/4"	32	41	0~0.7	0~0.4	35	50	185
PX-016-38	1-1/2"	38	48	0~0.6	0~0.4	45	50	300
PX-016-45	1-3/4"	45	56	0~0.6	0~0.4	48	40	400
PX-016-50	2"	50	62	0~0.6	0~0.3	54	40	440
PX-016-63	2-1/2"	63	80	0~0.4	0~0.3	53	20	650
PX-016-75	3"	75	92	0~0.3	0~0.3	62	20	800

